



GE  
Lighting

**19901 - GE Compact HIR™ PAR30**

**50PAR30HIR/FL25**

**Product Photo**



**GENERAL CHARACTERISTICS**

Base Description	Medium NP
Base Type	Pin/Plug-In
Filament	CC-8
Rated Life Hours-nominal	4000 h
Product Technology	Halogen
Bulb Shape	PAR30

**PHOTOMETRIC CHARACTERISTICS**

Beam Spread	25 deg
Center Beam Candle Pwr Candela	3200 cd
Nominal Initial Lumen per Watt	17
Initial Lumens-nominal	825 lm
Color Temperature	2810 K

**PRODUCT INFORMATION**

Product Code	19901
Description	50PAR30HIR/FL25
Alternative Unit Of Measure	EACH
Standard Package Quantity	15
Ean UPC	043168970471
Standard Package GTIN	00043168970471
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	15
Sales Unit	Each
UCC	043168199018
Alternative Unit Of Measure	CASE

**DIMENSIONS**

Diameter	3.75 in
----------	---------

**ELECTRICAL CHARACTERISTICS**

Input Voltage [nom]	120 V
Rated power (Watts)	50 W

**CAUTIONS & WARNINGS**

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Fire

- Keep combustible materials away from lamp.

Risk of Burn

- Allow lamp to cool before handling.

Risk of Electric Shock

- Turn power off before inspection installation or removal.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

- Do not use lamp if outer glass is scratched or broken.
- Do not use where directly exposed to water or outdoors without an enclosed fixture.