



<b>Description</b>	30W 120V Spiral 5500K 90+ CRI E26 Self Ballasted Compact Fluorescent
<b>Ordering Code</b>	48045
<b>UNSPSC Code</b>	39101619

## Specifications

<b>Voltage Rating</b>	120
<b>Watts</b>	30
<b>Base Type</b>	Medium Screw (E26)
<b>Bulb Type</b>	T-4
<b>MOL in/mm</b>	6.3/160
<b>MOD in/mm</b>	2.76/70
<b>Mercury Content (mg)</b>	3
<b>HG Form</b>	liquid
<b>Approx Initial Lumens</b>	1600
<b>CT deg K</b>	5500
<b>CRI</b>	93
<b>Rated Life</b>	10,000
<b>Special Desc</b>	Not for use with dimmers, electronic timers, photocells, totally enclosed fixtures, motion/occupancy sensors, or where directly exposed to water.
<b>Type Use</b>	Specialty: Photo, Digital Imaging
<b>Replaces</b>	Std 150W Incandescent
<b>Ambient Operating Temp Range</b>	-18° C (0° F) to 40° C (104° F)

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335